

# LabTecta® 66RDS

Radially Divided Bearing Protector



- Eliminate the cause of over 50% of bearing failures
- Extended bearing and equipment life
- LabTecta®66 contamination prevention technology
- No shaft wear or damage to equipment
- Easy installation

## LabTecta®66RDS – Radially Divided Seal




The AESSEAL® LabTecta®66RDS provides a quick and cost effective alternative to dismantling large equipment to fit bearing seals. It can be tailored to suit any specific application whether it is a new build project or retrofitted to existing equipment.


### Eliminate the cause of over 50% of bearing failures

A major study into equipment reliability has shown **48%** of all bearing failures are due to particle contamination of the bearing oil, with an additional **4%** due to corrosion caused by water contamination.

This gives a total of **52% of bearing failures** caused by contamination of the bearing oil. The LabTecta®66 product family can prevent these failures.



The LabTecta®66RDS combines the hugely successful contamination prevention technology of the LabTecta®66 range, with the ease of installation of a split-seal. As well as keeping contamination out, it is effective at keeping oil in: this means you save time and money by needing fewer oil changes.



Item	Description	Material
1	Split Rotary O Ring	Viton®
2	Split Rotary O Ring	Viton®
3	Rotary Half	Phosphor Bronze
4	Rotary Half	Phosphor Bronze
5	Capscrew	Stainless Steel
6	Energizing O Ring	Viton®
7	Shut-off Rotary O Ring	Viton®
8	Stator Half	Phosphor Bronze
9	Stator Half	Phosphor Bronze
10	Body O Ring	Viton®




## LabTecta®66RDS — Easy Installation

The unique design of the LabTecta®66RDS means installation problems are a thing of the past. The entire assembly comprises of only two split metal parts and five 'O' rings.


An additional option supplied by AESSEAL® is poppet type 'O' rings which means installation even in the tightest of places is relatively straight forward.

### 'No need for setting clips'

To ensure the LabTecta®66RDS is installed correctly, simply check the rotary face sits flush with the stator face.




Poppet 'O' ring



Correct installation 'made easy'

## LabTecta®66RDS — Alternative Designs

The LabTecta®66RDS is also available in several configurations including flange mounted, axial movement and internal air-purge, giving even greater flexibility for your application. For further technical information or to enquire about pricing and delivery contact the Bearing Protection Division.



# LabTecta®66RDS – Designed for Your Equipment

## Sketch Housing Dimensions:

Either use the “standard” diagram provided or sketch your own below.

**Dimensions:**

ØA (Shaft Ø): .....

ØB (Housing bore Ø): .....

ØC (First obstruction on face): .....

D (Max. insertion): .....

E (First obstruction): .....

## Application Data:

Equipment type: ..... Shaft horizontal or vertical: .....

Speed: ..... Bearing type: .....

Lubrication type / system: ..... Max. axial movement: .....

Complete the information above and send to:

UK Fax: **+44 (0) 1709 720788** USA Fax: **+1 865 531 0571** E-mail: [sales@labtecta.com](mailto:sales@labtecta.com)

Further information about the AESSEAL® LabTecta®66 range is available in the standard LabTecta®66 brochure.

E-mail: [sales@labtecta.com](mailto:sales@labtecta.com) to request a copy or download it from our website: [www.labtecta.com](http://www.labtecta.com)

For further information and safe operating limits contact our technical specialists at the locations below.



Use double mechanical seals with hazardous products.

Always take safety precautions:

- Guard your equipment
- Wear protective clothing

**WARNING**

### UK Sales & Technical advice:

AESSEAL plc  
 Mill Close  
 Bradmarsh Business Park  
 Rotherham, S60 1BZ, UK  
 Tel: +44 (0) 1709 369966  
 Fax: +44 (0) 1709 720788  
 E-mail: [seals@aessecal.com](mailto:seals@aessecal.com)  
[www.aessecal.com](http://www.aessecal.com)

AESSEAL plc is certified to ISO 9001, ISO 14001, ISO 29001, ISO 50001 and OHSAS 18001.

'Our purpose is to give our customers such exceptional service that they need never consider alternative sources of supply.'

INVESTOR IN PEOPLE

### USA Sales & Technical advice:

AESSEAL Inc.  
 355 Dunavant Drive  
 Rockford,  
 TN. 37853, USA  
 Tel: +1 865 531 0192  
 Fax: +1 865 531 0571  
 E-mail: [usa@aessecal.com](mailto:usa@aessecal.com)  
[www.aessecal.com](http://www.aessecal.com)

**Important:** Since the conditions and methods of use of this product are beyond our control, AESSEAL plc expressly disclaims any and all liability resulting or arising from any use of this product or reliance on any information contained in this document - AESSEAL plc standard conditions of sale apply. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. AESSEAL® is a Registered Trademark of AES Engineering Ltd, AESSEAL plc recognizes all trademarks and trademark names as the property of their owners.